



SERIE SMRS 19

SINGLETURN ABSOLUTE AND INCREMENTAL BLIND HOLLOW SHAFT ENCODER

SSI SSI
SSI + SinCos

BiSS BiSS-C
BiSS-C + SinCos

- Singleturn resolution up to 21 bits
- Incremental resolution 2048 SIN/COS
- External diameter 58 mm
- Blind hollow shaft $\varnothing$ 10 or 12 mm
- Operating temperature range up to 100°C
- Protection class IP54 according to DIN EN 60529
- Connection by cable (other cable length available)



Optical
Encoder



Absolute and
incremental
encoder



Electronic
output
SIN/COS



Vibration
and shock
resistant






IP 54



Temperature
range
+100°C



Express
Delivery



Drawing blind hollow shaft type 3, connection type 10, without flange

REFERENCE

Reference example: SMRS19-31101311S-17

Serie	Blind-Hollow shaft	Anti-rotation system	Connection	Interface	Code	IP	Power supply	Parameters config.	Absolute resolution	Special customer
SMRS19 -	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐
	3. $\varnothing$ 12 mm 4. $\varnothing$ 10 mm	1. None	10. Helicoidal cable 20. 30 cm cable + connector D-Sub 15p	1. SSI 2. SSI + 2048 SIN/COS 3. BiSS-C 4. BiSS-C + 2048 SIN/COS	1. Binary CW 2. Binary CCW 3. Gray (*) CW 4. Gray (*) CCW 5. BiSS (**)	1. IP54	1. 4...30 VDC 2. 5 VDC	S. Direction (*) R. Reset (*)	10. 10 bits 12. 12 bits 13. 13 bits 14. 14 bits 17. 17 bits 19. 19 bits 21. 21 bits	KD.Halogen-free cable

(*) Options only available for Interface type 1 (SSI) and 2 (SSI + 2048 SIN/COS).

(**) BiSS protocol allows to configure CRC, Alarm messages, Warnings, Sense, Reset and Absolute resolution by BUS.

Default configuration: Binary CW

Order your reference
Step file 3D

info@encoderhohner.com
service available in 24 h

Other extension cable options available with specific connectors mounted at the end of the cable for different market drives, on request.



SERIE SMRS 19

SINGLETURN ABSOLUTE AND INCREMENTAL BLIND HOLLOW SHAFT ENCODER

SSI / SSI + SinCos
BiSS-C / BiSS-C + SinCos

TECHNICAL SPECIFICATIONS

Materials	Housing: Aluminium Flange: Aluminium Shaft: Stainless Steel
Bearings	Ballraces
Bearings lifetime	1x10 ¹⁰ rev.
Maximum number of revolutions permitted mechanically	6000 rpm
Protection against dust and splashes according to DIN EN 60529	IP54
Rotor inertia moment	≤ 3x10 ⁻⁶ Kg·m ²
Starting torque at 20°C (68°F)	≤ 0,02 Nm
Maximum load permitted on axial shaft	40 N
Maximum load permitted on radial shaft	60 N
Weight approx.	0,4 Kg
Operating temperature range	-10°C to +100°C
Vibration according to DIN EN 60068-2-6	100 m/s ² (10Hz...2000Hz)
Shock according to DIN EN 60068-2-27	1000 m/s ² (6ms)
Consumption	≤ 90 mA
Power supply	5 VDC ±10% / 4...30 VDC
Direction (*)	Interface 1 and 2 (SSI): External controlled by cable Interface 3 and 4 (BiSS-C): Configurable by BUS
Reset (**)	Interface 1 and 2 (SSI): External controlled by cable Interface 3 and 4 (BiSS-C): Configurable by BUS
Linearity	± ½ LSB
Helicoidal cable	2 meters cable (other cable lengths available or connector mounted at the end of the cable, upon request)
Axial or radial connection	2 meters cable or industrial connector M23 (other cable lengths available on order) or 30 cm cable + connector D-Sub 15p

(*) Connecting DIR input to positive changes its direction.

(**) Connecting RESET input to positive will reset the encoder (Timeout: 15 ms).

SSI / BiSS INTERFACE

		
Electronic output	RS485	RS485
Max. load capability / channel	±20 mA	±20 mA
Resolution	10...19 bits 21 bits - Upon request	10, 12, 13, 14, 17, 19 bits
Code	Binary Gray	Binary
Clock frequency	50 kHz ... 2 MHz	50 kHz ... 10 MHz
Protocol	SSI	BiSS-C

INCREMENTAL OUTPUT


	
Electronic output	Differential 1 Vpp
Signal offset	2,5 VDC
Resolution	2048 ppr
Cutoff frequency (-3 db)	>500 kHz

SERIE SMRS 19

SINGLETURN ABSOLUTE AND INCREMENTAL BLIND HOLLOW SHAFT ENCODER

SSI / SSI + SinCos
BiSS-C / BiSS-C + SinCos

CONNECTION



	Cable (**) 6x2x0,14 mm ² 95.0008072	Cable (**) 6x2x0,14 mm ² Halogen-free cable up to 90°C 95.0008073	D-Sub 15p High density
GND	White	White	13
VCC	Brown	Brown	12
DATA+	Pink	Pink	7
DATA-	Grey	Grey	2
CLOCK+	Yellow	Yellow	6
CLOCK-	Green	Green	1
DIR or RESET	Red-Blue	Red-Blue	11
A+(cos)	Red	Red	8
B+(sin)	Black	Black	9
A-(cos)	Blue	Blue	3
B-(sin)	Violet	Violet	4
Shield*	Shield	Shield	Housing



(*) Shield connected to the encoder housing. It is recommended to connect the end of the wire shield to the ground of the equipment where the encoder is connected. $\perp$

(**) The recommended maximum cable length is 10 meters.

For longer lengths use connection option type 20 connection with extension accessories.

ANTI-ROTATION SYSTEMS DIMENSIONS

Flexible flange
90.1027



90.1027

